

In the Specification

Although not indicated by the Examiner, Applicant located a clerical error in the specification which requires amendment. On page 8, the paragraph beginning on line 16, please amend as follows:

The attachment device **10** may further be defined as having quick connect fittings **45a, 45b** on the air lines **40a, 40b** beyond the check valve **42a, 42b** and the regulator **44a, 44b** allowing for a quick connection of the air line **40a, 40b** to the inlet chucks **52a, 54b**. Similarly, the foam tubing **70a, 70b** may also be connected to the outlet chucks ~~**56r, 56l**~~ **56a, 56b** using quick connect fittings **75a, 75b**, to provide a quick disconnection and connection of the foam headers **50a, 50b** from the air lines **40a, 40b** and foam tubing **70a, 70b** for cleaning the system after use to remove the foaming solution **80** residue in the foam headers **50a, 50b**, bottles **60** and foam tubing **70a, 70b**. See FIG. 3. These quick connect fittings **45a, 45b, 75a, 75b** may also allow for the air line **40a, 40b** to be connected directly to the foam tubing **75a, 75b** using a quick connect fitting adapter (not shown) to purge the foam tubing **70a, 70b** of residual foam **84** in the foam tubing **70a, 70b** with air. The foam tubing **70a, 70b** should be flexible, which would allow them to remain attached to the boom sprayer apparatus **150** when the boom arms **152, 154** are folded into a stored position after use. Swimming pool hose has been found to be most suitable as the foam tubing **70a, 70b** or otherwise best presented as one inch clear plastic tubing to monitor the flow and quantity of foam being disposed to the vertical drop tubes **74a, 74b**.